



No.:

Date: 10-NOV-2017

DATA SHEET

Three-phase induction motor - Squirrel cage rotor

Customer :
Product line : W22 - Cast Iron Frame - High Efficiency - IE2

Frame : L112M
Output : 5.5 kW
Frequency : 50 Hz
Poles : 4
Full load speed : 1440 rpm
Slip : 4.00 %
Voltage : 230/400 V
Rated current : 20.2/11.6 A
Locked rotor current : 143/82.4 A
Locked rotor current (I_l/I_n) : 7.1
No-load current : 13.5/7.75 A
Full load torque : 36.5 Nm
Locked rotor torque : 270 %
Breakdown torque : 300 %
Design : ---
Insulation class : F
Temperature rise : 80 K
Locked rotor time : 11 s (hot)
Service factor : 1.00
Duty cycle : S1
Ambient temperature : -20°C - +40°C
Altitude : 1000 m
Degree of Protection : IP55
Approximate weight : 52 kg
Moment of inertia : 0.02077 kgm²
Noise level : 56 dB(A)

	D.E.	N.D.E.	Load	Power factor	Efficiency (%)
Bearings	6207 ZZ	6206 ZZ	100%	0.76	87.7
Regreasing interval	---	---	75%	0.68	87.7
Grease amount	---	---	50%	0.55	87.0

Notes:

Efficiencies according to the indirect method of IEC 60034-2-1:2007 with stray load losses determined from measurement.

Performed by

Checked